

Internal Over Veneer FD30 Fire Doors

Specifications

Fire Rating

FD30 44mm 30minute to BS476:Part 22: 1987 (CERTIFIRE CF5143)

Construction

Flush face with complementing hardwood lippings. Over veneered face with a Flaxboard core.

Door Codes

African Maple (Anegre)	MAPOVF
Ash	ASHOVF
Beech	BCHOVF
Koto	KOTOVF
Sapele	SAPOVF
White Oak	WOKOVF
Ecograde	ECCGF

Moisture Content

10% (+/-2%) in accordance with BS:EN942

Facings

0.5mm veneer

Components

Stiles:	N/A
Rails (outer):	N/A
Rails (inner):	N/A
Core:	Flaxboard
Lockblock:	Incorporated into the Flaxboard core
Lipping:	6mm complementing hardwood

Lock Area

Locks and handles maybe fitted centrally in height either side of the door, maximum dimensions specified on installation instructions provided.

Finish

Pre-finished no further decoration required to the two faces only touch up to the two long edges with clear lacquer after trimming.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door is not allowed to be trimmed due to the BWF-CERTIFIRE fire certification label and manufacturing identifications.

Installation Note:

The doors have been tested to BS476 pt 22:1987 and are approved by BWF-CERTIFIRE of being capable of achieving 30 minute fire resistance when fitted in accordance with the installation instruction delivered with every door.

All doors must be fitted with intumescent strips to the head and sides of the door leaf or frame.

Cutting of apertures or glazing is not permitted and invalidates the fire certification.

