



CERTIFICATE OF APPROVAL
No CF 819

This is to certify that, in accordance with
TS00 General Requirements for Certification of Fire Protection Products
The undermentioned products of

**ZMR LTD TRADING AS MILLENNIUM DOOR
SYSTEMS**

**Unit 10, Spartan Industrial Centre, Brickhouse Lane, Great Bridge,
West Midlands, B70 0DH**
Tel: 0121 521 3550 Fax: 0121 521 3578
www.mbp.co.uk

Have been assessed against the requirements of the Technical Schedule(s)
denoted below and are approved for use subject to the conditions
appended hereto:

CERTIFIED PRODUCT

**FD30 Strebord 44
Timber Doorsets**

TECHNICAL SCHEDULE

**TS10 Fire Resisting Door
Assemblies with Non
Metallic Leaves**

Signed and sealed for and on behalf of CERTIFIRE

A handwritten signature in black ink, appearing to be "K. Knight".

Sir Ken Knight
Chairman - Management Council

Issued: 21 December 2010
Valid to: 20 December 2015

Page 1 of 3



Only valid when authentic
CERTIFIRE Seal is in place



CERTIFICATE No CF 819

ZMR LTD TRADING AS MILLENNIUM DOOR SYSTEMS

ZMR Ltd trading as Millennium Door Systems FD30 Strebord 44 Timber Doorsets

1. This approval relates to the use of the above doorsets in providing fire resistance of 30 minutes integrity as defined in BS 476: Part 22: 1987. Subject to the undermentioned conditions, the doors would be expected to meet the relevant requirements of BS 5588 for FD30 doorsets when used in accordance with the provisions therein.
2. This certification is designed to demonstrate compliance of the product or system specifically with Approved Document B (England and Wales), Section 2 of the Technical Standards (Scotland), Technical Booklet E (N. Ireland). If compliance is required to other regulatory or guidance documents there may be additional considerations or conflict to be taken into account.'
3. The doors are approved on the basis of:
 - i) Initial type testing
 - ii) Audit testing at the frequency specified in TS10
 - iii) A design appraisal against TS10
 - iv) Production surveillance under ISO 9001: 2008
 - v) Inspection and surveillance of factory production control
4. The doors comprise cellulosic cored leaves in various finishes for use with timber frames, with intumescent edge seals (ITT FD30).
5. This approval is applicable to both complete doorsets and door leaves. Where the door is not supplied in a completely fitted form it is a condition of this approval that an agreed data sheet accompanies the product and is complied with in its entirety. Failure to do so will invalidate this approval and may jeopardise the fire performance of the door.
6. This approval is applicable to latched and unlatched, single-acting, single and double-leaf, ITT assemblies, at leaf dimensions up to those given in Table 1.
7. Hardware items, including closing devices and intumescent edge seals, shall be CERTIFIRE approved or otherwise as specified in the data sheet.
8. The doorset shall be mechanically fixed to wall constructions having a fire resistance of at least 30 minutes.

A handwritten signature in black ink, appearing to be "K. M. M.", located below the "Signed" text.



CERTIFICATE No CF 819

ZMR LTD TRADING AS MILLENNIUM DOOR SYSTEMS

ZMR Ltd trading as Millennium Door Systems FD30 Strebord 44 Timber Doorsets

9. Labels to the BWF/CERTIFIRE design referencing ZMR Ltd trading as Millennium Door Systems, CERTIFIRE and CERTIFIRE Ref. No. CF 819 and FD30 fire resistance shall be fixed to each door in the prescribed position.
10. The approval relates to on going production. Product and/or its immediate packaging is identified with the manufacturer's name, the product name or number, the CERTIFIRE name or name and mark, together with the CERTIFIRE certificate number and application where appropriate.

Table 1
Size Envelope

Doorset configuration	Maximum Height (mm)	Maximum Width (mm)	Area (m ²)
Single-Acting, Single-Leaf Unlatched	2478 (at 936 wide)	1086 (at 2136 high)	2.32
Single-Acting, Single-Leaf Latched	2925 (at 1072 wide)	1161 (at 2700 high)	3.13
Single-Acting, Double-Leaf Latched / Unlatched	2470 (at 902 wide)	1065 (at 2100 high)	2.23

A handwritten signature in black ink, appearing to be "K. M. M.", located below the "Signed" text.